falmec

VERSO COMFORT **EAN code 8034122371474**



Photograph is for information purposes only. May not correspond to the selected version

Version	Wall - 55 cm - Black matt - 800 m3/h
Design	Falmec Lab
Collection	Design

TECHNICAL FEATURES

Materials/Finishes	Black matt glass
Technology	Comfort-Silence technology for noise reduction
Features	Double suction area (frontal and lower) Opening frontal
Control	Touch control Remote control (optional) Dialogue system
Function	Extracting/Filtering
Chimney	Optional chimney
Lighting	Dynamic Light (2700K - 5600K) Dimmable lighting Strip LED 2x1,7 W - 2700 K / 5600 K
Filters	Metallic grease filter, removable and washable Combined Carbon.Zeo Microtech regenerable filter (optional)
Dimensions	55 cm
Minimum Electric hob distance	52 cm
Minimum Gas hob distance	52 cm
Notes	Available from October 2026

CONNECTION AND CONSUMPTION FUNCTIONS

Maximum consumption	280 W
Voltage/Frequency	220-240V 50-60Hz

MOTOR


Motor	800 m^3/h
Maximum capacity	521 m^3/h I.E.C.61591
Maximum sound level	61 dB (A)re1pW I.E.C. 60704-2-13
Energy class	A


WEIGHTS AND VOLUMES

Gross weight	19.4 kg
Net weight	15.2 kg
Volume	0.19 m3
Packaging dimensions	L 710 x H 452 x P 595 mm


falmec

VERSO COMFORT **EAN code 8034122371474**





Side view




Optional chimney

Optional accessories

Code	*Description*
KACL.1059	Conveyer for air outlet (Ø150)
105080053	Remote control
KACL.1074	Carbon.Zeo Microtech filter (Verso Comfort)
FDS 100 Schabus	
KCAIN.00#N	Chimney - Black

falmec

VERSO COMFORT **EAN code 8034122371474**



PF		
S	Falmec Lab	
M	Wall - 55 cm - Black matt - 800 m3/h	
AEC	45.90	kWh/a
EEC	A	
FDE	29.30	
FDEC	A	
LE	12.70	
LEC	D	
GFE	82	
GFEC	C	
Qmin	291	m^3 /h
Qmax	521	m^3 /h
Qboost	644	m^3 /h
SPEmin	47	dBa
SPEmax	61	dBa
SPEboost	65	dBa
PO		
PS	0.28	W
PI		
F	0.90	
EEI	51.10	
Qbep	289	m^3 /h
Pbep	607	Pa
Qboost	644	m^3 /h
Wbep	132	W
WL	3.50	W
Emiddle	44	lux
Lwa-SPEmax	61	dBa

PF_Scheda prodotto conforme a 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m^3/h) at min speed in normal use / Qmax_Air flow (in m^3/h) at max speed in normal use / Qboost_Air flow (in m^3/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airbone acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps).
PI_Additional information according to 66/2014 Calculation methods: EN 61591:2020 F_Time increase factor / EEI_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.

rev. 04/11/2026